

## Material Safety Data Sheet

### Section 1 - Product Identification

Product Name: OXYNUL RP-5598

#### Hazard Rating

	Health	Fire	Reactivity	
NFPA Code:	1	2	0	
0=Least	1=Slight	2=Moderate	3=High	4=Extreme

FOR CHEMICAL EMERGENCY - Spill, leak, fire, exposure or accident  
Call CHEMTREC 800-424-9300

### Section 2 - Hazardous Ingredients / Identity Information

Specific Identity; Common Names	OSHA PEL	ACGIH TLV	Other
---------------------------------	----------	-----------	-------

Proprietary Formula - Specific Chemical Identities Have Been Withheld

064742-47-8

Hydrotreated Light Petroleum Distillates	100 ppm	-	TWA(8-hr) 525 mg/m3
--	---------	---	------------------------

64742-52-5

Severely hydrotreated heavy naphthenic distillates	5mg/m3	5mg/m3	
Mineral Oil	(mist)	(mist)	

64742-88-7

Aliphatic Petroleum Distillates	100ppm	100ppm	TWA(8hr) 350mg/cum
---------------------------------	--------	--------	-----------------------

### Section 3 - Physical/Chemical Characteristics

Appearance	Amber liquid
Boiling Point, Deg. F	Not Known
Evaporation Rate Ether=1	Slower than
Odor	Solvent
Solubility in water	Negligible
Vapor Density (Air=1)	Not Known
Vapor Pressure	Not Known
Pounds per Gallon	6.872
Specific Gravity	0.825

### Section 4 - Fire and Explosion Hazard Data

Flash Point, PMCC: 140F Flammable Limits: LEL-Not Known UEL-Not Known

Extinguishing Media: Foam, dry chemical, water fog, carbon dioxide. Do not use a direct stream of water.

Special Fire Fighting Procedures: Cool fire exposed containers with water.

Do not enter a confined fire space without full bunker gear and NIOSH approved supplied air breathing apparatus.

Unusual Fire and Explosion Hazards: Vapors are heavier than air and may travel along the ground. Avoid heat, spark and open flame. Do not cut, weld or puncture on or near this container even when empty.

### Section 5 - Reactivity Data

Stability - Stable.

Incompatibility - Strong acids. Strong bases. Strong oxidizing agents. Selected amines.

Hazardous Decomposition Products - Oxides of carbon. Oxides of sulfur.

continued...



## Material Safety Data Sheet

...continued

Hazardous Polymerization - Will not occur.

Other - Not Applicable.

---

### Section 6 - Health Hazard Data

Routes of Entry: Inhalation-yes Skin-yes Ingestion-yes

Health Hazards :

Health hazards for components to this mixture are listed below:

(Acute and Chronic Overexposure)

Eyes - Burning. Irritation. Redness. Tearing.

Skin - Prolonged and repeated contact can defat the skin which may result in dryness, dermatitis, and cracking of the skin.

Repeated or prolonged contact may cause defatting, oil acne, irritation or allergic reaction in sensitive individuals.

Inhalation - Irritation.

Signs of nervous system depression (e.g. headache, drowsiness, dizziness, loss of coordination, and fatigue).

Ingestion - Nausea. Stomach discomfort.

Pulmonary aspiration hazard if swallowed and vomiting occurs.

Signs And Symptoms of Exposure - As Noted Above.

Medical Conditions Generally Aggravated By Exposure -

Preexisting skin and respiratory conditions may be aggravated by exposure.

Other Precautions - NA

Other -

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage (sometimes referred to as solvent or painter's syndrome). Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.

Carcinogenicity NTP-No IARC-No OSHA-No

Emergency and First Aid Procedures:

Inhalation - remove to fresh air. If breathing is difficult, give oxygen.

If breathing is stopped, begin artificial respiration. Get medical attention.

Skin contact - wash skin thoroughly with soap and water. Remove and wash contaminated clothing before reuse. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of the injury.

Eye contact - flush with water for at least 15 minutes or until irritation subsides, get medical attention.

Ingestion - DO NOT induce vomiting; get medical attention immediately.

---

### Section 7 - Precautions for Safe Handling and Use

Steps to be Taken in Case Material is Released or Spilled:

Eliminate ignition sources. Dike area. Recover free product. Add a dry

---

continued...



## Material Safety Data Sheet

...continued

absorbent material to spill area.

Waste Disposal Method: Dispose by methods consistent with local state and federal regulations.

Precautions to be Taken in Handling and Storing: Keep containers tightly closed. Use and store this product with adequate ventilation. Avoid inhalation of vapors and personal contact with the product. To dissipate static electricity during transfer, ground and/or bond both containers. Since emptied containers retain product residue, follow warnings even after container is emptied. Residue or vapors may explode on ignition; do not cut, drill, grind or weld on or near container even when empty.

Other Precautions:  
Not Applicable

---

### Section 8 - Control Measures

Respiratory Protection: Not normally required. Use NIOSH approved supplied air breathing equipment if vapors are excessive.

Ventilation: Local Exhaust : Not normally required.  
Mechanical (General): Use general ventilation.

Protective Gloves: Use chemical-resistant gloves, if needed, to avoid skin contact.

Eye Protection: Use splash goggles or face shield when eye contact may occur.

Other Protective Clothing or Equipment: To prevent repeated or prolonged skin contact, wear impervious apron/clothing and boots.

Work/Hygienic Practices: Minimize breathing vapor, mist or fumes. Wash skin with soap and water after contact. Launder contaminated clothing.

---

### Section 9 - Regulatory Information

#### DOT Information

DOT Proper Shipping Name: COMBUSTIBLE LIQUID, NOS(Contains 70% Petroleum Naphtha)

DOT Hazard Code: COMBUSTIBLE LIQUID

UN Number: 1993

#### Section 313 Supplier Notification

This product contains the following chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372):

CAS#	Common Name	Weight%
	None	

This information should be included in all MSDSs that are copied and distributed for this material.


---

Prepared according to the OSHA Hazard Communication Standard (29 CFR 1910.1200) by Coolant Control Inc.

---

The information set forth herein is furnished free of charge and is based on technical data that we believe to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of the information. Nothing herein is to be taken as a license to operate under or a recommendation to infringe any patents.

---



**COOLANT  
CONTROLS**

Product Code: 5598COATO

Revision Date: 11/15/2007

Revised By: MSDS Dept.

Page: 4

## Material Safety Data Sheet

---

End of MSDS

---