

5353 Spring Grove Avenue, Cincinnati, OH 45217 USA 513-471-8770 www.coolantcontrol.com

Material Safety Data Sheet

Section 1 - Product Identification

Product Name: Cutrite3300

Hazard Rating

| | | | | |
|---------|----------|------------|------------|-----------|
| | Health | Fire | Reactivity | |
| Code: | 1 | 1 | 0 | |
| 0=Least | 1=Slight | 2=Moderate | 3=High | 4=Extreme |

Section 2 - Hazardous Ingredients / Identity Information

| | | | |
|---------------------------------|----------|-----------|-------|
| Specific Identity; Common Names | OSHA PEL | ACGIH TLV | Other |
|---------------------------------|----------|-----------|-------|

Proprietary Formula - Specific Chemical Identities Have Been Withheld


| | | | |
|--|--------|--------|-----------------------|
| 64742-52-5 | | | |
| Severely hydrotreated heavy naphthenic distillates | 5mg/m3 | 5mg/m3 | |
| Mineral Oil | (mist) | (mist) | |
| 68526-86-3 | | | |
| Alcohols C11-C14-ISO-, C13-RICH | - | - | TWA= 50ppm (Exxon) |
| 68551-13-3 | | | |
| Alcohols, C12-15, Ethoxyl | - | - | |
| 7732-18-5 | | | |
| Water | - | - | |
| 8002-26-4 | | | |
| Distilled tall oil | - | - | |

Section 3 - Physical/Chemical Characteristics

| | |
|-------------------------------|----------------------|
| Appearance | Amber liquid |
| Boiling Point, Deg. F | Not Known |
| Evaporation, BuAcetate=1 | Slower than |
| Odor | Mild |
| pH Diluted in water | 9.2 @5% |
| Solubility in water | Emulsifies |
| Vapor Density (Air=1) | Not Known |
| Vapor Pressure | Not Known |
| CRT43 | not found in RAWMAT. |
| Press any key to continue ... | |
| EZMULZ4400N | not found in RAWMAT. |
| Press any key to continue ... | |
| Pounds per Gallon | 0.0000 |
| Specific Gravity | 0.0000 |

Section 4 - Fire and Explosion Hazard Data

Flash Point COC: >350F Flammable Limits: LEL-Not Known UEL-Not Known
 Extinguishing Media: Foam, dry chemical, water fog, carbon dioxide. Do not use a direct stream of water.
 Special Fire Fighting Procedures: Cool fire exposed containers with water. Do not enter a confined fire space without full bunker gear and NIOSH approved supplied air breathing apparatus.
 Unusual Fire and Explosion Hazards: Not Applicable



5353 Spring Grove Avenue, Cincinnati, OH 45217 USA 513-471-8770 www.coolantcontrol.com

Material Safety Data Sheet

...continued

Section 5 - Reactivity Data

Stability - Stable.

Incompatibility - Strong acids. Strong bases. Oxidizing agents. Strong reducing agents.

Hazardous Decomposition Products - Aldehydes. Ammonia. Formaldehyde. Iodine vapors. Organic compounds. Oxides of carbon. Oxides of nitrogen. Oxides of sulfur.

Hazardous Polymerization - Will not occur.

Other - Not Applicable.

Section 6 - Health Hazard Data

Routes of Entry: Inhalation=yes Skin=yes Ingestion=yes

Health Hazards :

The health hazards listed below are for components to this mixture. The active ingredients are diluted in mineral oil in this mixture and the severity of the listed health hazards for this product may be reduced. This product is designed to be diluted significantly with water before product use. The severity of these health hazards may be reduced further at usage concentrations. (Acute and Chronic Overexposure)

Eyes - Corneal clouding. Severe irritation. Redness. Swelling.

Skin - Severe irritation. Prolonged contact may cause slight irritation. Prolonged and repeated contact can defat the skin which may result in dryness, dermatitis, and cracking of the skin.

Persons sensitized by contact with rosin may develop an allergic reaction.

Inhalation - Severe irritation. Vapors may cause irritation.

Ingestion - Diarrhea. Severe gastrointestinal irritation. May causes gastrointestinal disturbances. Nausea. Stomach discomfort. Vomiting. Pulmonary aspiration hazard if swallowed and vomiting occurs.

Signs And Symptoms of Exposure - As Noted Above.

Medical Conditions Generally Aggravated By Exposure - None Known.

Other Precautions - NA

Other - NA

Carcinogenicity NTP-No IARC-No OSHA-No

Emergency and First Aid Procedures:

Inhalation - remove to fresh air. If breathing is difficult, give oxygen. If breathing is stopped, begin artificial respiration. Get medical attention.

Skin contact - wash skin thoroughly with soap and water. Remove and wash contaminated clothing before reuse. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of the injury.


Eye contact - flush with water for at least 15 minutes or until irritation subsides, get medical attention.

Ingestion - DO NOT induce vomiting; get medical attention immediately.

Section 7 - Precautions for Safe Handling and Use

Steps to be Taken in Case Material is Released or Spilled:

continued...



5353 Spring Grove Avenue, Cincinnati, OH 45217 USA 513-471-8770 www.coolantcontrol.com

Material Safety Data Sheet

...continued

Dike area. Recover free product. Add a dry absorbent material to spill area.

Waste Disposal Method: Dispose by methods consistent with local state and federal regulations.

Precautions to be Taken in Handling and Storing: Keep containers tightly closed. Use and store this product with adequate ventilation. Avoid inhalation of vapors and personal contact with the product. To dissipate static electricity during transfer, ground and/or bond both containers. Since emptied containers retain product residue, follow warnings even after container is emptied. Residue or vapors may explode on ignition; do not cut, drill, grind or weld on or near container even when empty.

Other Precautions:
Not Applicable

Section 8 - Control Measures

Respiratory Protection: Not normally required. Use NIOSH approved supplied air breathing equipment if vapors are excessive.

Ventilation: Local Exhaust : Not normally required.
Mechanical (General): Use general ventilation.

Protective Gloves: Use chemical-resistant gloves, if needed, to avoid skin contact.

Eye Protection: Use splash goggles or face shield when eye contact may occur.

Other Protective Clothing or Equipment: To prevent repeated or prolonged skin contact, wear impervious apron/clothing and boots.

Work/Hygienic Practices: Minimize breathing vapor, mist or fumes. Wash skin with soap and water after contact. Launder contaminated clothing.

Section 9 - Regulatory Information

DOT Information

DOT Proper Shipping Name: None

DOT Hazard Code: None

UN Number: None

TSCA

All components of this product are included in the TSCA inventory or are regulated under FIFRA.

Section 313 Supplier Notification

This product contains the following chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372):


| CAS# | Common Name | Weight% |
|------|-------------|---------|
|------|-------------|---------|

This information should be included in all MSDSs that are copied and distributed for this material.

Prepared according to the OSHA Hazard Communication Standard
(29 CFR 1910.1200) by

The information set forth herein is furnished free of charge and is based

continued...



**COOLANT
CONTROL INC.**

Product Code: CUTRITE3300

Revision Date: 02/09/2009

Revised By: MSDS Dept.

Page: 4

5353 Spring Grove Avenue, Cincinnati, OH 45217 USA 513-471-8770 www.coolantcontrol.com

Material Safety Data Sheet

...continued

on technical data that we believe to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of the information. Nothing herein is to be taken as a license to operate under or a recommendation to infringe any patents.

End of MSDS
