

5353 Spring Grove Avenue, Cincinnati, OH 45217 USA 513-471-8770

Material Safety Data Sheet

Section 1 - Product Identification

Product Name: Oxynul RP-5511

Hazard Rating

	Health	Fire	Reactivity	
NFPA Code:	1	2	0	
0=Least	1=Slight	2=Moderate	3=High	4=Extreme

FOR CHEMICAL EMERGENCY - Spill, leak, fire, exposure or accident
Call CHEMTREC 800-424-9300

Section 2 - Hazardous Ingredients / Identity Information

Specific Identity; Common Names	OSHA PEL	ACGIH TLV	Other
---------------------------------	----------	-----------	-------

Proprietary Formula - Specific Chemical Identities Have Been Withheld

064742-47-8

Hydrotreated Light Petroleum Distillates	100 ppm	-	TWA(8-hr) 525 mg/m3
--	---------	---	------------------------

64742-88-7

Aliphatic Petroleum Distillates	100ppm	100ppm	TWA(8hr) 350mg/cum
---------------------------------	--------	--------	-----------------------

Section 3 - Physical/Chemical Characteristics

Appearance	Amber liquid
Boiling Point, Deg. F	Not Known
Evaporation, BuAcetate=1	Slower than
Odor	Mild
Solubility in water	Negligible
Vapor Density (Air=1)	Not Known
Vapor Pressure	Not Known
Specific Gravity	0.930
Pounds per gallon	7.745

Section 4 - Fire and Explosion Hazard Data

Flash Point, PMCC:	145F	Flammable Limits: LEL-Not Known	UEL-Not Known
--------------------	------	---------------------------------	---------------

Extinguishing Media: Foam, dry chemical, water fog, carbon dioxide. Do not use a direct stream of water.

Special Fire Fighting Procedures: Cool fire exposed containers with water. Do not enter a confined fire space without full bunker gear and NIOSH approved supplied air breathing apparatus.

Unusual Fire and Explosion Hazards: Vapors are heavier than air and may travel along the ground. Avoid heat, spark and open flame. Do not cut, weld or puncture on or near this container even when empty.

Section 5 - Reactivity Data

Stability - Stable.


Incompatibility - Strong acids. Strong bases. Strong oxidizing agents. Selected amines.

Hazardous Decomposition Products - Oxides of carbon.

Hazardous Polymerization - Will not occur.

Other - Not Applicable.

Section 6 - Health Hazard Data



5353 Spring Grove Avenue, Cincinnati, OH 45217 USA 513-471-8770

Material Safety Data Sheet

...continued

Routes of Entry: Inhalation-yes Skin-yes Ingestion-yes

Health Hazards :

Health hazards for components to this mixture are listed below:
(Acute and Chronic Overexposure)

Eyes - Burning. Irritation. Redness. Tearing.

Skin - Mild irritation.

Prolonged and repeated contact can defat the skin which may result in dryness, dermatitis, and cracking of the skin.

Inhalation - Irritation.

Signs of nervous system depression (e.g. headache, drowsiness, dizziness, loss of coordination, and fatigue).

Ingestion -

Pulmonary aspiration hazard if swallowed and vomiting occurs.

Signs And Symptoms of Exposure - As Noted Above.

Medical Conditions Generally Aggravated By Exposure -

Preexisting skin and respiratory conditions may be aggravated by exposure.

Other Precautions - NA

Other -

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage (sometimes referred to as solvent or painter's syndrome). Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.

Carcinogenicity NTP-No IARC-No OSHA-No

Emergency and First Aid Procedures:

Inhalation - remove to fresh air. If breathing is difficult, give oxygen.

If breathing is stopped, begin artificial respiration. Get medical attention. Skin contact - wash skin thoroughly with soap and water. Remove and wash contaminated clothing before reuse.

Eye contact - flush with water for at least 15 minutes or until irritation subsides, get medical attention.

Ingestion - Aspiration hazard. DO NOT induce vomiting; get medical attention immediately.

Section 7 - Precautions for Safe Handling and Use

Steps to be Taken in Case Material is Released or Spilled:


Eliminate ignition sources. Dike area. Recover free product. Add a dry absorbent material to spill area.

Waste Disposal Method: Dispose by methods consistent with local state and federal regulations.

Precautions to be Taken in Handling and Storing: Keep containers tightly closed. Use and store this product with adequate ventilation. Avoid inhalation of vapors and personal contact with the product. To dissipate static electricity during transfer, ground and/or bond both containers. Since emptied containers retain product residue, follow warnings even after container is emptied. Residue or vapors may explode on ignition; do not cut, drill, grind or weld on or near container even when empty.

Other Precautions:

continued...



5353 Spring Grove Avenue, Cincinnati, OH 45217 USA 513-471-8770

Material Safety Data Sheet

...continued

Not Applicable

Section 8 - Control Measures

Respiratory Protection: Not normally required. Use NIOSH approved supplied air breathing equipment if vapors are excessive.
Ventilation: Local Exhaust : Not normally required.
Mechanical (General): Use general ventilation.
Protective Gloves: Use chemical-resistant gloves, if needed, to avoid skin contact.
Eye Protection: Use splash goggles or face shield when eye contact may occur.
Other Protective Clothing or Equipment: To prevent repeated or prolonged skin contact, wear impervious apron/clothing and boots.
Work/Hygienic Practices: Minimize breathing vapor, mist or fumes. Wash skin with soap and water after contact. Launder contaminated clothing.

Section 9 - Regulatory Information

DOT Information

DOT Proper Shipping Name: FLAMMABLE LIQUID, N.O.S., (PETROLEUM DISTILLATES)
DOT Hazard Code: PGIII
UN Number: UN1993

TSCA

All components of this product are included in the TSCA inventory or are regulated under FIFRA.

Section 313 Supplier Notification

This product contains the following chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community RightTo-Know Act of 1986 (40 CFR 372):

CAS#	Common Name	Weight%
	None	

This information should be included in all MSDSs that are copied and distributed for this material.

Prepared according to the OSHA Hazard Communication Standard (29 CFR 1910.1200) by The Cincinnati Vulcan Company.

The information set forth herein is furnished free of charge and is based on technical data that Vulcan believes to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of the information. Nothing herein is to be taken as a license to operate under or a recommendation to infringe any patents.

End of MSDS
