



COOLANT CONTROL INC.

MATERIAL SAFETY DATA SHEET

Vuldra FT 303

HEAVY - DUTY
SYNTHETIC DRAWING COMPOUND

Material Identification and Use

PRODUCT IDENTIFIER: **Vuldra FT 303**
PRODUCT USE: Water Soluble Heavy - Duty Drawing Compound
MANUFACTURER'S NAME: Coolant Control Inc
MANUFACTURER'S ADDRESS: 5353 Spring Grove Ave
Cincinnati, OH 45217
MANUFACTURER'S PHONE: (513) 471-8770
DATE PREPARED: 1/24/07

Hazardous Ingredient Information

<u>CHEMICAL IDENTITY</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>Other Limits</u>	<u>Percent Optional</u>	<u>CAS Number</u>
Phosphoric Acid, 2 - Ethylhexyl Ester	3 mg/M ³	3 mg/M ³		< 5.0	12645-31-7
Triethanolamine	5 mg/M ³	5 mg/M ³		< 5.0	120-71-6
Potassium Hydroxide	2 mg/m ³	2 mg/m ³		< 5.0	1310-58-3

Physical Data for Product

BOILING POINT 212° F
VAPOR PRESSURE (mm Hg.) Not Determined
VAPOR DENSITY (Air =1) Not Determined
SOLUBILITY IN WATER Complete
APPEARANCE AND ODOR Viscous Milky Opaque Liquid
SPECIFIC GRAVITY (H2O=1) 1.025 @ 60° F
MELTING POINT N/A
EVAPORATION RATE (Butyl Acetate=1) << 1

Fire and Explosion Hazard of Product

FLASHPOINT AND METHOD
OF DETERMINATION > 300° F (ASTM D92)
LOWER EXPLOSION LIMIT
(% By Volume) Not determined
UPPER EXPLOSION LIMIT
(% By Volume) Not determined
MEANS OF EXTINCTION Use water spray, dry chemical, foam or carbon dioxide. Water or foam may cause frothing. Use water spray to keep fire-exposed containers cool. Water spray may be used to flush spills away from exposures. Minimize breathing gasses, vapor,

fumes, or decomposition products. Use supplied-air breathing equipment for enclosed or confined spaces, or as otherwise needed.

FOR FIRE

Self contained breathing equipment and chemical resistant clothing recommended.

EXPLOSION DATA

Extreme heat may cause sealed containers to rupture. Cool fire exposed containers with water spray.

Reactivity Data

CHEMICAL STABILITY

Stable

CONDITIONS TO AVOID

None known

INCOMPATIBLE MATERIALS

None known

HAZARDOUS DECOMPOSITION PRODUCTS

Oxides of carbon, nitrogen, and phosphorous from combustion.

HAZARDOUS POLYMERIZATION CONDITIONS TO AVOID

Will not occur
None Special

Health Hazard Data

ROUTES OF ENTRY

SKIN CONTACT

Not likely under normal usage.

INHALATION

Not likely under normal usage.

INGESTION

Not likely under normal usage.

HEALTH HAZARDS

Direct contact with the eyes can cause irritation, redness or blurred vision. Product may be slightly to moderately irritating to the skin.

CARCINOGENICITY

Non carcinogenic

SYMPTOMS OF EXPOSURE

Contact with the skin may cause transient dermal irritation or dryness.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Not determined

SPECIFIC FIRST AID PROCEDURES

EYES

Flush with clear water for 15 minutes.

SKIN CONTACT

Wash thoroughly with mild soap and water.

Contact a Physician if irritation persists.

INGESTION

Has laxative effect resulting in rapid elimination.

Do not induce vomiting. Consultation with a physician is recommended.

Precautions for Safe Handling and Use

LEAK AND SPILL PROCEDURES

Contain spill. Collect and return large amounts to shipping container. Rinse spill area with soap and water. Keep product out of sewers and watercourses. Advise authorities if product has entered sewers, watercourses or extensive land areas.

