



**COOLANT  
CONTROL<sup>INC.</sup>**

*The right chemistry...*

*...the right solution*

## Product Bulletin

# Vulclean FC-5551

## Heavy Duty Concentrated Floor Cleaner

### Description

**Vulclean FC-5551** is a non-flammable heavy-duty liquid detergent concentrate designed to be diluted with water for general maintenance cleaning. **Vulclean FC-5551** is highly recommended for use in the hand cleaning of soiled shop machinery and because of its fast drying and low foam characteristics, it is also recommended for use in mechanical floor scrubbing equipment.

### Performance Benefits

- Safe on all metal, concrete, paint, plastic and rubber seals
- Effectively removes tire marks and heavy oils such as drawing and stamping compounds
- No rinsing required at typical concentrations
- Dries fast to minimize slippery surfaces

### Recommended Applications

**Vulclean FC-5551** is typically used in mechanical floor scrubbers at a level of 2% to 5%.

**Vulclean FC-5551** can be used to clean out machine sumps and pipes by adding 1% to 2% by volume to the coolant prior to dumping.

**Vulclean FC-5551** should be diluted at a rate of 2 to 12 ounces per gallon for hand wiping and pressure washing applications.

### Typical Characteristics

Appearance	Green liquid with a mild odor
pH (2% dilution)	10.8 to 12.2
Specific Gravity	1.03 to 1.07
Flash Point	None
RI Factor	4.55