

Vulclean FC-5551

Heavy-duty floor and maintenance cleaner

Description

Vulclean FC-5551 is a non-flammable heavy-duty liquid detergent concentrate designed to be diluted with water for general maintenance cleaning. **Vulclean FC-5551** is highly recommended for use in the hand cleaning of soiled shop machinery and, because of its fast drying and low foaming characteristics, it is also recommended for use in mechanical floor scrubbing equipment.

Performance Benefits

- Safe on all metal, concrete, paint, plastic and rubber seals
- Effectively removes tire marks and heavy oils such as drawing and stamping compounds
- No rinsing required at typical concentrations
- Dries fast to minimize slippery surfaces

Recommended Applications & Dilutions

	Concentration	Temperature Range
Floor Scrubber	2% to 5%	Ambient to 120°F
Pressure Sprayer	Not recommended	-
Mop & Bucket	0.5% to 5%	Ambient to 120°F

Characteristics

Properties	Unit	Test Method	Value
Appearance of Concentrate	-	Visual	Clear green liquid
Appearance of Dilution	-	Visual	Clear green liquid
Odor	-	-	Mild
pH (typical operating range)	-	-	11.8
Density @ 15°C	lbs/gal	-	8.7
Nitrites	-	-	No
Silicates	-	-	Yes
Phenols	-	-	No

Concentration Control

Refractometer Multiplier: 4.55

Concentration = Refractive Index X Refractometer Multiplier

Refractometer Reading	% Concentration
.4	2
.7	3
.9	4
1.1	5

